



NOTES :

- 1 : FLAME PROOF GROUPS - I,IIA & IIB AS PER IS:2148
- 2 : DEGREE OF PROTECTION - IP:65 AS PER IS:2147
- 3 : MATERIAL - CAST ALUMINIUM ALLOY LM6
- 4 : EARTHING - 1 No. INTERNAL & 2 Nos. EXTERNAL SCREWS ARE PROVIDED
- 5 : GASKET - NEOPRENE
- 6 : FINISH - LIGHT GREY TO SHADE 631 OF IS:5 (EPOXY POWDER COATED)
- 7 : TERMINAL BLOCK - 12 Nos. 2.5 Sq.mm
- 8 : CABLE ENTRY - 2 Nos. 3/4"ET ENTRY
- 9 : PUSH BUTTONS -
 "OFF" PUSH BUTTON WILL BE OF PADLOCKABLE/KEYLOCKABLE TYPE
 "ON" PB WILL BE OF SHROUD TYPE - GREEN COLOR
- 10 : VIEWING GLASS 72x72mm AMMETER

SPECIAL NOTES :

- * JUST BY CHANGING COVERS VARIOUS COMBINATIONS CAN BE OBTAINED
COMBINATION CAN BE OBTAINED WITH TWO CHAMBERS ALSO
- * JUST BY CHANGING COVER WITH DOMED COVER, THE HEIGHT WILL BE 210mm OVERALL DIMENSION : ±10mm

CUSTOMER		TITLE			
PROJECT		FLP-WP ON/OFF PUSHBUTTON,INDICATING LAMP WITH AMMETER			
CONSULTANT		SCG Ex d TECH PVT. LTD.			
DRAWN	SM	CHENNAI-600 032			
CHECKED	DKK				
APPROVED	GK				
SCALE	NTS	FILE REF.	CAT.NO.	CMRS CERT No.	GA.DRG.No.
		CS/187	DOLS/99187	CMRI/TC/P/H846 DATED 30.06.99	SCG/OF0000/CS187/0001
					REV. DATE
					0 14/11/05