



NOTES :

- 1 : FLAME PROOF GROUPS - IIA & IIB AS PER IS:2148
- 2 : DEGREE OF PROTECTION - IP:65 AS PER IS:2147
- 3 : MATERIAL - CAST ALUMINIUM ALLOY LM6
- 4 : EARTHING - 1 No. INTERNAL & 2 Nos. EXTERNAL SCREWS ARE PROVIDED
- 5 : GASKET - NEOPRENE
- 6 : FINISH - LIGHT GREY TO SHADE 631 OF IS:5 (EPOXY POWDER COATED)
- 7 : TERMINAL BLOCK - 4 Nos. 2.5 Sq.mm (JUNCTION BOX)
- 8 : CABLE ENTRY - 4 Nos. 3/4"ET (OR) 1"ET ENTRY
- 9 : 1 No. 16A DP/TP ISOLATOR

OVERALL DIMENSION : ±10mm

CUSTOMER		TITLE					
PROJECT		FLP-WP 16A DP/TP ISOLATOR SCG Ex d TECH PVT. LTD. CHENNAI-600 032					
CONSULTANT							
DRAWN	SM						
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. IS/105	CAT.NO. RI/99105	CMRS CERT No. CMRI/TC/H507 DATED 02.04.97.	GA.DRG.No. SCG/OF0000/IS105/0001	REV. 0	DATE 14/11/05