



- 1 : FLAME PROOF GROUPS– IIA & IIB AS PER IS: 2148/1981.
- 2 : WEATHER PROOF – IP: 65 AS PER IS:2147/1962.
- 3 : MATERIAL – ALUMINIUM ALLOY LM6.
- 4 : EARTHING – 1 No. INTERNAL & 2 Nos. EXTERNAL (M6).
- 5 : GASKET – NEOPRENE.
- 6 : FINISH – LIGHT GREY EPOXY SHADE NO. 631 OF IS:5.
- 7 : TERMINAL – 4 Nos. 2.5/4 Sq.mm STUD TYPE
- 8 : CABLE ENTRY – 2 Nos. 3/4” ET
- 9 : SWITCH – 16A – 32A DP/TP ISOLATOR
- 10 : THE PLUG CANNOT BE REMOVED WHEN THE SWITCH IS IN THE 'ON' POSITION AND CAN BE WITHDRAWN, ONLY WHEN THE SWITCH IS IN THE 'OFF' POSITION.

OVERALL DIMENSION : ±10mm

CUSTOMER			TITLE				
PROJECT			FLP-WP 16A / 32A INTERLOCKED SWITCH PLUG & SOCKET SCG Ex d TECH PVT. LTD.,CHENNAI. CHENNAI				
CONSULTANT							
DRAWN	SM						
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. PS/1010	CAT.NO. SC/991010	CMRS CERT No. CMRI/TC/H12 DT. 11.08.94	GA.DRG.No. SCG/OF0000/PS1010/0001	REV. 0	DATE 14/11/05