



- 1 - FLAME PROOF - GROUPS-IIA & IIB AS PER IS: 2148/1981.
- 2 - WEATHER PROOF - IP: 65 AS PER IS:2147/1962.
- 3 - MATERIAL - CAST ALUMINIUM ALLOY LM6.
- 4 - FINISH - LIGHT GREY EPOXY SHADE NO. 631 OF IS:5.
- 5 - EARTHING - 1NO. INTERNAL & 2 NOS. EXTERNAL (M6).
- 6 - GASKET - NEOPRENE.
- 7 - CABLE ENTRY - 2 Nos. 1"ET AT BOTTOM
WITH 1 No. GLAND & 1 No. PLUG
- 8 - TERMINAL - 5 Nos. CBTM4 STUD TYPE, CW/ELMEX MAKE
- 9 - 16A - 32A TPN ISOLATOR
- 10 - THE PLUG CANNOT BE REMOVED WHEN THE SWITCH IS IN THE 'ON' POSITION AND CAN BE WITHDRAWN, ONLY WHEN THE SWITCH IS IN THE 'OFF' POSITION.

OVERALL DIMENSION ±10mm.

CUSTOMER		TITLE FLP-WP 16A-32A SWITCH SOCKET & PLUG COMBINED (3P+N+E)					
PROJECT							
CONSULTANT							
DRAWN	SM	SCG Ex d TECH PVT. LTD., CHENNAI.					
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. PS/187	CAT.NO. SC/99187	CMRS CERT No. CMRI/TC/P/H846 DT. 30.06.99	GA.DRG.No. SCG/OF0000/PS187/0001	REVN 0	DATE 14/11/05