



NOTES :

- 1 : FLAME PROOF – GROUPS–IIA & IIB AS PER IS: 2148/1981.
- 2 : WEATHER PROOF – IP: 65 AS PER IS:2147/1962.
- 3 : MATERIAL – CAST ALUMINIUM ALLOY LM6.
- 4 : FINISH – LIGHT GREY EPOXY SHADE NO. 631 OF IS:5.
- 5 : EARTHING – 1NO. INTERNAL & 2 NOS. EXTERNAL (M6).
- 6 : GASKET – NEOPRENE.
- 7 : CABLE ENTRY – 2 Nos. 1” ET
- 8 : TERMINAL block – 6 Nos. CBTM4 STUD TYPE
- 9 : 16A – 32A DP/TPN ISOLATOR
- 10 : THE PLUG CANNOT BE REMOVED WHEN THE SWITCH IS IN THE 'ON' POSITION AND CAN BE WITHDRAWN, ONLY WHEN THE SWITCH IS IN THE 'OFF' POSITION.

OVERALL DIMENSION ±10mm.

CUSTOMER		TITLE						
PROJECT		FLP-WP 16A-32A TWIN PLUG & SOCKET SCG Ex d TECH PVT. LTD., CHENNAI.						
CONSULTANT								
DRAWN	SM							
CHECKED	DKK							
APPROVED	GK							
SCALE	NTS	FILE REF. PS/187	CAT.NO. SC/99187	CMRS CERT No. CMRI/TC/P/H846 DT. 30.06.99	GA.DRG.No. SCG/OF0000/PS187/0001	REVN 0	DATE 14/11/05	