



**NOTES**

- 1 : MATERIAL – ALUMINIUM ALLOY LM6
- 2 : DEGREE OF PROTECTION – IP 65 AS PER IS:2147.
- 3 : EARTHING – 1 No. INSIDE & 2 Nos. OUTSIDE SCREWS ARE PROVIDED.
- 4 : GASKET – NEOPRENE
- 5 : FINISH – LIGHT GREY TO SHADE 631 OF IS:5 (EPOXY POWDER COATED)
- 6 : CABLE ENTRY – 3 Nos. 3/4"ET ENTRY (AT BOTTOM)
- 7 : TERMINAL BLOCKS – 8 Nos. 2.5SQMM, CW/EQUI.
- 8 : STOP PUSH BUTTON WILL BE PADLOCKABLE/KEYLOCKABLE TYPE, RED COLOUR
- 9 : SSW – AUTO/MANUAL (or) LOCAL REMOTE SELECTOR SWITCH

OVERALL DIMENSION ARE ±10mm

CUSTOMER		TITLE				
PROJECT		<b>WEATHERPROOF ON/OFF PUSHBUTTON WITH SWITCH</b>				
CONSULTANT						
DRAWN	SM					
CHECKED	DKK	<b>SCG Ex d TECH PVT. LTD.</b>				
APPROVED	GK	<b>CHENNAI-600 032.</b>				
SCALE	NTS	FILE REF. WP/03	CAT No. SCG/WP03	GA.DRG.No. SCG/OF0000/WP03/001	REV 0	DATE 14/11/05